

CHASSIS PLANS



CPL-A1617

ENCLOSURE

- 1U (1.71") x 16" deep
- *Lightweight all aluminum chassis*
- *Designed to satisfy military, industrial and commercial requirements*
- *Compact enclosure for limited depth installation*
- *Continuous Friction Hinges*
- *Built-in cable management*
- *Slides included*

DISPLAY

- *17" Diagonal Active Matrix TFT LCD*
- *Features Samsung display technology*
- *SXGA 1208 x 1024 @ 60Hz native resolution*
- *Fast response time for real-time display*

VIDEO CONTROLLER

- *Standard aRGB Input*
- *OSD (On Screen Display) for Monitor Setup and Control*

OPTIONAL FEATURES / OPTIONS

- *Abrasion Resistant Lens Cover*
- *Protective Glare Filters*
- *Customer Specified Paint Color*
- *Customer Logo*

COMPANION DISPLAY

The companion CPL-A1617U display is identical except it is intended for the monitor to swing down. Thus, mounting the CPL-A1617U under the CPL-A1617 provides a double high display utilizing only 2U of rack space.

The CPL-A1617 is a high performance rack mount 1U 17" TFT LCD display with 1280 X 1024 SXGA resolution that is only 16" deep. The lightweight chassis is all aluminum and is optimized for portable applications. The display offers 250nit brightness, 350:1 contrast, and 75 degree viewing angle for exceptional viewability. An anti-glare hard coating minimizes reflections making images much more clear. The aspect ratio is 4:3 with a Pixel Pitch of only 0.264mm. It will display 16.7 million colors (True Color).

The monitor pivots upward from a flat position of 0 degrees to an upright position of 119 degrees.

The CPL-A1617 provides an analog RGB signal input.

As with all Chassis Plans products, a wide variety of custom options are available including custom paint color, customer logo, anti-glare shield, sun light filters, etc.

Designed and manufactured in the USA.



The Original Industrial Computer Source®

Chassis Plans® · 8295 Aero Place · San Diego · CA · 92123
 Phone (858) 571-4330 · Fax (858) 571-6146
 saleseng@chassisplans.com
 www.chassisplans.com
 © 2006 Chassis Plans

SPECIFICATION

ENCLOSURE

1U x 19" (wide) x 16" (deep)
Fits 20"-36" Rack
Weight: 12.0lbs
Lightweight Aluminum Construction
Color: Powder coated black, light texture
(Custom colors and logos available)

DISPLAY

17" TFT LCD w/ antiglare hard coating
Display Colors: 16.7 Million
Response Time (Tr / Tf): 5/20 ms
Viewing Angle: 75/70/60/60 deg
Contrast Ratio: 350:1 typical
Brightness: 250cd/m2 typical
Pixel Pitch: 0.264mm x 0.264mm
Power: EPA Energy Star, VESA DPMS

DISPLAY RESOLUTION

Max Resolution: SXGA 1280x1024 @ 60Hz
12 Display Modes: VGA to SXGA
Horizontal Frequency: 15-80KHz
Vertical Frequency: 50-77Hz

ON SCREEN DISPLAY (OSD)

Contrast, Brightness, Auto-setting, Clock /
Phase, Horizontal & Vertical Position / Ex-
pansion / OSD, Text & Graph Mode Selec-
tion, Color Temp, Recall

CERTIFICATIONS

FCC-A, CE
Optional UL, CSA, CE/ENC, DHHS,
NORDICS, TUV/GS, 1S09241-3,
FCC-B, MPR II, TCO 95

CONNECTORS:

aRGB in: 15-pin high density DB15
DC Power In: 2-Pin 2x5.5 Power Plug

POWER CONSUMPTION

Input Voltage: 12VDC Nominal
Normal: 60W (front LED Green)
DPM Stand-by/Suspend: <5W (front LED Amber)
DPM Off: <3W (front LED Amber)
Power Switch Off: <1W (front LED Off)
Power Supply: Remote "brick" switching supply
Power Supply Size: 4.8" x 2.4" x 1.5", 12oz
Power Input: 100-240VAC, 50/60Hz 1.8A
Optional -48VDC input available

ENVIRONMENTAL

Operating conditions:
Temperature: 0 to 50 deg C
Humidity: 20% to 95% non-condensing
Altitude: 10,000 feet

Storage conditions:

Temperature: -25 to 60 deg C
Humidity: 5% to 95% non-condensing
Altitude: 24,000 feet

SHIPPING

Weight: 37lbs
Shipping Box - 23" x 6" x 33"

Ordering Code	Description
CPL-A1617-13A	No touch screen, aRGB input



The Original Industrial Computer Source®

